

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: FIREPLACE #EU34857F
UFI	: WP4P-KCCP-X00D-PYQ9
Product code	: EU34857F
Type of product	: Perfumes, fragrances
Product group	: Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Main use category	: Professional use, Industrial use
Industrial/Professional use spec	: For professional use only Industrial
Use of the substance/mixture	: Perfumes, fragrances
Function or use category	: Odour agents

1.3. Details of the supplier of the safety data sheet

FRENCH COLOR & FRAGRANCE INTERNATIONAL GmbH
 Mittlerer Weg 35
 DE 79424 Auggen
 Germany
 T 49-7631-931-8900
SDS@frenchcolor.com, www.frenchcolor.com

1.4. Emergency telephone number

Emergency number	: 1-800-255-3924; +01-813-248-0585; China:+400-120-0751; Mexico:+01-800-099-0731; Brazil: +0-800-591-6042; India: +000-800-100-4086
------------------	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 1	H314
Skin sensitisation, Category 1	H317
Aspiration hazard, Category 1	H304
Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects. May cause an allergic skin reaction.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Contains

: CUPRESSUS FUNEBRIS WOOD OIL; Cedryl acetate; Cedarwood oil, Virginia; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone; Vertofix; Eugenol; Cinnamic aldehyde; Cedar leaf oil; COUMARIN; Lemon oil ; Cinnamalva; Linalool

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H304 - May be fatal if swallowed and enters airways. H314 - Causes severe skin burns and eye damage. H317 - May cause an allergic skin reaction. H411 - Toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P272 - Contaminated work clothing should not be allowed out of the workplace. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	5.4 – 10.7	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
CUPRESSUS FUNEBRIS WOOD OIL	CAS-No.: 85085-29-6 EC-No.: 285-360-9	3.5 – 7	Skin Corr. 1, H314 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Cedryl acetate	CAS-No.: 77-54-3 EC-No.: 201-036-1	3 – 6	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Skin Sens. 1B, H317
Cedarwood oil, Virginia	CAS-No.: 8000-27-9 EC-No.: 285-370-3	1.8 – 3.5	Asp. Tox. 1, H304 Aquatic Chronic 1, H410
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone	CAS-No.: 54464-57-2 EC-No.: 259-174-3 REACH-no: 01-2119489989-04	1.8 – 3.5	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 1, H410
Sandal Mysore Core	CAS-No.: 28219-60-5 EC-No.: 248-907-2	1.1 – 2.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Vanillin	CAS-No.: 121-33-5 EC-No.: 204-465-2 REACH-no: 01-2119516040-60	0.8550095 – 1.7820198	Eye Irrit. 2, H319

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Vertofix	CAS-No.: 32388-55-9 EC-No.: 251-020-3 REACH-no: 01-2119969651-28	0.6 – 1.25	Skin Sens. 1B, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Eugenol	CAS-No.: 97-53-0 EC-No.: 202-589-1 REACH-no: 01-2119971802-33	0.5 – 1	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-45	0.5 – 1	Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1A, H317 Aquatic Chronic 3, H412
Cedar leaf oil	CAS-No.: 8007-20-3 EC-No.: 290-370-1 REACH-no: 01-2120763401-62	0.2 – 0.35	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Skin Sens. 1, H317 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
COUMARIN	CAS-No.: 91-64-5 EC-No.: 202-086-7 REACH-no: 01-2119943756-26	0.1 – 0.25	Acute Tox. 4 (Oral), H302 Skin Sens. 1B, H317
Camphene	CAS-No.: 79-92-5 EC-No.: 201-234-8	0.1 – 0.15	Flam. Sol. 2, H228 Eye Irrit. 2, H319 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
Citrus medica limonum (Lemon) peel oil	CAS-No.: 8008-56-8 EC-No.: 284-515-8	0.1 – 0.15	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Cinnamalva	CAS-No.: 1885-38-7 EC-No.: 217-552-5	0.1 – 0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Sens. 1B, H317
Allyl heptanoate	CAS-No.: 142-19-8 EC-No.: 205-527-1 REACH-no: 01-2119488961-23	0.1 – 0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 3, H412
Linalool	CAS-No.: 78-70-6 EC-No.: 201-134-4 EC Index-No.: 603-235-00-2 REACH-no: 01-2119474016-42	0.1 – 0.1	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1B, H317
Ethyl acetoacetate substance with national workplace exposure limit(s) (RO)	CAS-No.: 141-97-9 EC-No.: 205-516-1	0.1 – 0.1	Not classified

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Dipropylene glycol monomethyl ether substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2	0.000254 – 0.000508	Not classified
Toluene substance with national workplace exposure limit(s) (AT, BE, BG, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GI, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, PL, PT, RO, SE, SI, SK, NO, CH, TR); substance with a Community workplace exposure limit	CAS-No.: 108-88-3 EC-No.: 203-625-9 EC Index-No.: 601-021-00-3	≤ 0.000006	Not classified

Specific concentration limits:

Name	Product identifier	Specific concentration limits (%)
Cinnamic aldehyde	CAS-No.: 104-55-2 EC-No.: 203-213-9 EC Index-No.: 606-155-00-6 REACH-no: 01-2119935242-45	(0.001 < C < 0.01) EUH208 (0.01 ≤ C < 0.1) Skin Sens. 1; H317 (0.1 ≤ C < 100) Skin Sens. 1A; H317

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Allow affected person to breathe fresh air. Allow the victim to rest.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see Get medical advice/attention. on this label). If skin irritation occurs: Get medical advice/attention. Wash with plenty of water/.... Get medical advice/attention. Wash contaminated clothing before reuse. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Sand. Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Section 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Keep only in the original container in a cool, well ventilated place away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container closed when not in use. Store locked up. Store in a well-ventilated place. Keep cool.
Incompatible products	: Strong bases. Strong acids.
Incompatible materials	: Sources of ignition. Direct sunlight.
Storage temperature	: 25 °C
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Store in a closed container.
Packaging materials	: Do not store in corrodable metal.

Switzerland

Storage class (LK) : LK 6.1 - Toxic materials

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

National occupational exposure and biological limit values

Dipropylene glycol monomethyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	308 mg/m ³ 50 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	307 mg/m ³ (mixed isomers) 50 ppm (mixed isomers)
MAK (OEL STEL)	614 mg/m ³ (isomers mixtures) 100 ppm (isomers mixtures)
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ 50 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ 50 ppm
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	308 mg/m ³ 50 ppm
OEL chemical category	Skin notation
Cyprus - Occupational Exposure Limits	
OEL TWA	308 mg/m ³

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	270 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Denmark - Occupational Exposure Limits	
OEL TWA	309 mg/m ³ 50 ppm
OEL STEL	618 mg/m ³ 100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ 50 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	310 mg/m ³ 50 ppm
OEL chemical category	Potential for cutaneous absorption
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	308 mg/m ³ (restrictive limit) 50 ppm (restrictive limit)
OEL chemical category	Risk of cutaneous absorption
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	310 mg/m ³ (isomer mixture) 50 ppm (isomer mixture)
Gibraltar - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ 50 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³ 100 ppm
OEL STEL	900 mg/m ³ 150 ppm
OEL chemical category	skin - potential for cutaneous absorption
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	308 mg/m ³

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
Ireland - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ ((2-Methoxymethylethoxy)propanol)
	50 ppm ((2-Methoxymethylethoxy)propanol)
OEL STEL	924 mg/m ³ (calculated (2-(2-Methoxypropoxy)-1-propanol)
	150 ppm (calculated (2-(2-Methoxypropoxy)-1-propanol)
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous exposure
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	300 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	50 ppm (2-(2-Methoxypropoxy)-propanol)
TPRV (OEL STEL)	450 mg/m ³ (2-(2-Methoxypropoxy)-propanol)
	75 ppm (2-(2-Methoxypropoxy)-propanol)
OEL chemical category	Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	300 mg/m ³
	48.7 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	240 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol and 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
NDSch (OEL STEL)	480 mg/m ³ (mixture of isomers: 1-(2-Methoxy-1-methylethoxy)propan-2-ol, 1-(2-Methoxy-2-methylethoxy)propan-2-ol, 2-(2-Methoxy-1-methylethoxy)propan-1-ol)
Portugal - Occupational Exposure Limits	
OEL TWA	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	150 ppm

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL chemical category	Skin notation
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Slovenia - Occupational Exposure Limits	
OEL TWA	308 mg/m ³
	50 ppm
OEL STEL	308 mg/m ³
	50 ppm
OEL chemical category	Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	308 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous absorption
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	300 mg/m ³
	50 ppm
KGV (OEL STEL)	450 mg/m ³
	75 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	308 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	924 mg/m ³ (calculated)
	150 ppm (calculated)
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	300 mg/m ³
	50 ppm
Korttidsverdi (OEL STEL)	375 mg/m ³ (value calculated)
	75 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	300 mg/m ³ (aerosol, vapour)

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Dipropylene glycol monomethyl ether (34590-94-8)	
	50 ppm (aerosol, vapour)
KZGW (OEL STEL)	300 mg/m ³ (aerosol, vapour)
	50 ppm (aerosol, vapour)
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	50 ppm (Dipropylene glycol methyl ether)
Toluene (108-88-3)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	192 mg/m ³
	50 ppm
IOEL STEL	384 mg/m ³
	100 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
MAK (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Belgium - Occupational Exposure Limits	
OEL TWA	77 mg/m ³
	20 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin, Skin notation
Bulgaria - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
Bulgaria - Biological limit values	
BLV	1.6 mmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of exposure or end of work shift
Croatia - Occupational Exposure Limits	
GVI (OEL TWA)	192 mg/m ³
	50 ppm
KGVI (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Croatia - Biological limit values	
BLV	1 mg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of the work shift 20 ppm Parameter: Toluene - Medium: final exhaled air - Sampling time: during exposure 2.5 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine) 1 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: at the end of the work shift (calculated on the average Creatinine value of 1.2 g/L urine)
Cyprus - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ 50 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	Skin-potential for cutaneous absorption
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	200 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Czech Republic - Biological limit values	
BLV	1.6 µmol/mmol Creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1000 µmol/mmol Creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.) 1.5 mg/g creatinine Parameter: o-Cresol - Medium: urine - Sampling time: end of shift (after hydrolysis) 1600 mg/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (exposure testing using the o-Cresol parameter to precisely measure Toluene exposure is needed if the value of Hippuric acid is between 1600 and 2500 mg/g of Creatinine, no additional testing is needed if the Hippuric acid value is >2500 mg/g of Creatinine as work exposure to Toluene will have highly exceeded the PEL value.)
Denmark - Occupational Exposure Limits	
OEL TWA	94 mg/m ³ 25 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	Potential for cutaneous absorption
Estonia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ 50 ppm
OEL STEL	384 mg/m ³ 100 ppm
OEL chemical category	Skin notation
Finland - Occupational Exposure Limits	
HTP (OEL TWA)	81 mg/m ³

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
	25 ppm
HTP (OEL STEL)	380 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Finland - Biological limit values	
BLV	500 nmol/L Parameter: Toluene - Medium: blood - Sampling time: in the morning after a working day
France - Occupational Exposure Limits	
VLEP 8h (OEL TWA)	76.8 mg/m ³ (restrictive limit)
	20 ppm (restrictive limit)
VLEP CT (OEL STEL)	384 mg/m ³ (restrictive limit)
	100 ppm (restrictive limit)
OEL chemical category	Reproductive Toxin category 2, Risk of cutaneous absorption
France - Biological limit values	
BLV	20 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of workweek (Semi-quantitative (ambiguous interpretation)) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift (per the Authority, the values for this substance must be decided and/or determined on a case by case basis. Guidance for the calculation of and interpretation of values is provided in the source)
Germany - Occupational Exposure Limits (TRGS 900)	
AGW (OEL TWA)	190 mg/m ³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
	50 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed)
Chemical category	Skin notation
Germany - Biological limit values (TRGS 903)	
Biological limit value	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: immediately after exposure 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of exposure or shift 1.5 mg/l Parameter: o-Cresol (after hydrolysis) - Medium: urine - Sampling time: at the end of the shift, in case of long-term exposure after several previous shifts
Gibraltar - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Greece - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	190 mg/m ³
CK (OEL STEL)	384 mg/m ³
OEL chemical category	Potential for cutaneous absorption
Ireland - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Potential for cutaneous absorption
Italy - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL chemical category	skin - potential for cutaneous absorption
Latvia - Occupational Exposure Limits	
OEL TWA	50 mg/m ³
	14 ppm
OEL chemical category	skin - potential for cutaneous exposure
Latvia - Biological Exposure Indices	
BEI	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: at the end of exposure (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 75 µg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift (for assessment of long-term exposure, samples are taken at the end of a shift after several previous shifts) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: at the end of exposure or shift (after hydrolysis)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	192 mg/m ³
	50 ppm
TPRV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Reproductive toxin, Skin notation
Luxembourg - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Malta - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Possibility of significant uptake through the skin
Netherlands - Occupational Exposure Limits	
TGG-8u (OEL TWA)	150 mg/m ³
	39 ppm
TGG-15min (OEL STEL)	384 mg/m ³
	100 ppm
Poland - Occupational Exposure Limits	
NDS (OEL TWA)	100 mg/m ³
NDSch (OEL STEL)	200 mg/m ³
Portugal - Occupational Exposure Limits	
OEL TWA	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
OEL STEL	384 mg/m ³ (indicative limit value)
	100 ppm (indicative limit value)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen, skin - potential for cutaneous exposure indicative limit value
Romania - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
Romania - Biological limit values	
BLV	2 g/l Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift 3 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA)	192 mg/m ³
	50 ppm
NPHV (OEL C)	384 mg/m ³ (also biological monitoring considered)
OEL chemical category	Potential for cutaneous absorption
Slovakia - Biological limit values	
BLV	600 µg/l Parameter: Toluene - Medium: blood - Sampling time: end of exposure or work shift 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: after all work shifts (for long-term exposure) 1.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of exposure or work shift 2401 mg/g creatinine Parameter: Hippuric acid - Sampling time: end of exposure or work shift

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
Slovenia - Occupational Exposure Limits	
OEL TWA	192 mg/m ³
	50 ppm
OEL STEL	384 mg/m ³
	100 ppm
OEL chemical category	Category 2, Potential for cutaneous absorption
Spain - Occupational Exposure Limits	
VLA-ED (OEL TWA)	192 mg/m ³ (indicative limit value)
	50 ppm (indicative limit value)
VLA-EC (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	skin - potential for cutaneous absorption
Spain - Biological limit values	
BLV	0.6 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift 0.05 mg/l Parameter: Toluene - Medium: blood - Sampling time: start of last shift of workweek 0.08 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	192 mg/m ³
	50 ppm
KGV (OEL STEL)	384 mg/m ³
	100 ppm
OEL chemical category	Skin notation
United Kingdom - Occupational Exposure Limits	
WEL TWA (OEL TWA)	191 mg/m ³
	50 ppm
WEL STEL (OEL STEL)	384 mg/m ³
	100 ppm
WEL chemical category	Potential for cutaneous absorption
Norway - Occupational Exposure Limits	
Grenseverdi (OEL TWA)	94 mg/m ³
	25 ppm
Korttidsverdi (OEL STEL)	141 mg/m ³ (value calculated)
	37.5 ppm (value calculated)
OEL chemical category	Skin notation
Switzerland - Occupational Exposure Limits	
MAK (OEL TWA)	190 mg/m ³
	50 ppm
KZGW (OEL STEL)	760 mg/m ³
	200 ppm

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
OEL chemical category	Skin notation, Category 2 reproductive toxin
Switzerland - BAT	
BAT	600 µg/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 6.48 µmol/l Parameter: Toluene - Medium: whole blood - Sampling time: end of shift 2 g/g creatinine Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) Parameter: Hippuric acid - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 0.5 mg/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 4.62 µmol/l Parameter: o-Cresol - Medium: urine - Sampling time: end of shift, and after several shifts (for long-term exposures) 75 µg/l Parameter: Toluol - Medium: urine - Sampling time: end of shift
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	20 ppm
ACGIH® chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)
Ethyl acetoacetate (141-97-9)	
Romania - Occupational Exposure Limits	
OEL TWA	100 mg/m ³
	19 ppm
OEL STEL	200 mg/m ³
	38 ppm

8.2. Exposure controls

Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protection equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Personal protective equipment symbol(s):



Eye and face protection

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin protection

Skin and body protection:

Wear suitable protective clothing

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hand protection:

Protective gloves. Wear protective gloves.

Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate mask

Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Conforms to standard.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: Not available
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: 0.000296716 mm Hg (calculated value)
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: ≈ 0.95
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

Other safety characteristics

VOC content : 1.201574 % (calculated value)(CARB VOC) (%w/w)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions. Not established.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7). Direct sunlight. Extremely high or low temperatures.

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

benzyl benzoate (120-51-4)

LD50 oral rat	> 2000 mg/kg (Source: ECHA_API)
LD50 oral	1160 mg/kg
LD50 dermal rabbit	4000 mg/kg (Source: NLM_CIP)

Cedryl acetate (77-54-3)

LD50 oral rat	44750 mg/kg (Source: NLM_CIP)
---------------	-------------------------------

Cedarwood oil, Virginia (8000-27-9)

LD50 oral rat	> 5 g/kg (Source: NLM_CIP)
---------------	----------------------------

Vanillin (121-33-5)

LD50 dermal rabbit	> 5010 mg/kg (Source: OECD_SIDS)
LD50 dermal	2600 mg/kg

Vertofix (32388-55-9)

LD50 oral	4500 mg/kg
LD50 dermal rabbit	> 5000 mg/kg (Source: ECHA_API)

Eugenol (97-53-0)

LD50 oral rat	1930 mg/kg (Source: NZ_CCID)
LD50 oral	2500 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.58 mg/l/4h

Cinnamic aldehyde (104-55-2)

LD50 oral rat	2220 mg/kg (Source: NLM_CIP)
LD50 oral	2220 mg/kg
LD50 dermal rabbit	1260 mg/kg (Source: EPA_HPVP)
LD50 dermal	1260 mg/kg

Cedar leaf oil (8007-20-3)

LD50 oral rat	830 mg/kg (Source: NLM_CIP)
LD50 oral	830 mg/kg
LD50 dermal	4100 mg/kg

COUMARIN (91-64-5)

LD50 oral rat	> 5000 mg/kg (Source: JAPAN_GHS)
---------------	----------------------------------

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

COUMARIN (91-64-5)	
LD50 dermal rat	293 mg/kg (Source: ECHA_API)
Dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5.35 g/kg (Source: NLM_HSDB)
LD50 dermal rabbit	9500 mg/kg (Source: NLM_CIP)
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg (Source: JAPAN_GHS)
LD50 dermal rabbit	12000 mg/kg (Source: JAPAN_GHS)
LC50 Inhalation - Rat	12.5 mg/l/4h
Camphene (79-92-5)	
LD50 oral rat	5600 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
Citrus medica limonum (Lemon) peel oil (8008-56-8)	
LD50 oral rat	2840 mg/kg (Source: NLM_CIP)
Cinnamalva (1885-38-7)	
LD50 oral	100 mg/kg
LD50 dermal	1100 mg/kg
Allyl heptanoate (142-19-8)	
LD50 oral rat	500 mg/kg (Source: NLM_CIP)
LD50 oral	218 mg/kg
LD50 dermal rabbit	810 mg/kg (Source: ECHA_API)
LD50 dermal	810 mg/kg
Linalool (78-70-6)	
LD50 oral rat	2790 mg/kg (Source: NLM_CIP)
LD50 oral	2790 mg/kg
LD50 dermal rabbit	5610 mg/kg (Source: ECHA_API)
Ethyl acetoacetate (141-97-9)	
LD50 oral rat	3980 mg/kg (Source: NLM_CIP)
LD50 dermal rabbit	> 5000 mg/kg (Source: NLM_CIP)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Assumed to cause serious eye damage
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Eugenol (97-53-0)	
IARC group	3 - Not classifiable
COUMARIN (91-64-5)	
IARC group	3 - Not classifiable

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
benzyl benzoate (120-51-4)	
Viscosity, kinematic	7.456 mm ² /s
Toluene (108-88-3)	
Hydrocarbon	Yes
Camphene (79-92-5)	
Hydrocarbon	Yes

11.2. Information on other hazards

Other information

Potential adverse human health effects and symptoms : Based on available data, the classification criteria are not met

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
NOEC (chronic)	0.168 mg/l
Vanillin (121-33-5)	
LC50 - Fish [1]	53 – 61.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	88 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
NOEC (acute)	10000 mg/kg (Exposure time: 42 Days - Species: Eisenia foetida [soil dry weight])
Eugenol (97-53-0)	
LC50 - Fish [1]	13 mg/l (Exposure time: 96 h - Species: Danio rerio [semi-static] Source: ECHA)
Dipropylene glycol monomethyl ether (34590-94-8)	
LC50 - Fish [1]	> 10000 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	1919 mg/l (Exposure time: 48 h - Species: Daphnia magna)
Toluene (108-88-3)	
LC50 - Fish [1]	15.22 – 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through] Source: EPA)
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static] Source: EPA)
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Toluene (108-88-3)	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	12.5 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	> 433 mg/l (Species: Pseudokirchneriella subcapitata)
Camphene (79-92-5)	
LC50 - Fish [1]	0.72 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [flow-through] Source: IUCLID)
LC50 - Fish [2]	150 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static] Source: IUCLID)
EC50 - Crustacea [1]	22 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)
Linalool (78-70-6)	
LC50 - Fish [1]	27.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static] Source: ECHA)
EC50 - Crustacea [1]	20 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	88.3 mg/l (Species: Desmodesmus subspicatus)
Ethyl acetoacetate (141-97-9)	
LC50 - Fish [1]	298 mg/l (Exposure time: 96 h - Species: Pimephales promelas Source: IUCLID)
LC50 - Fish [2]	290 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss Source: IUCLID)
EC50 - Crustacea [1]	646 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 72h - Algae [1]	> 500 mg/l (Species: Desmodesmus subspicatus)
12.2. Persistence and degradability	
FIREPLACE #EU34857F	
Persistence and degradability	Not established.
benzyl benzoate (120-51-4)	
Persistence and degradability	May cause long-term adverse effects in the environment.
CUPRESSUS FUNEBRIS WOOD OIL (85085-29-6)	
Persistence and degradability	Rapidly degradable
Cedryl acetate (77-54-3)	
Persistence and degradability	Rapidly degradable
Cedarwood oil, Virginia (8000-27-9)	
Persistence and degradability	Rapidly degradable
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Persistence and degradability	Rapidly degradable
Sandal Mysore Core (28219-60-5)	
Persistence and degradability	Rapidly degradable
Vanillin (121-33-5)	
Persistence and degradability	Not established.
Vertofix (32388-55-9)	
Persistence and degradability	Rapidly degradable

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Eugenol (97-53-0)	
Persistence and degradability	Rapidly degradable
Cinnamic aldehyde (104-55-2)	
Persistence and degradability	Rapidly degradable
Cedar leaf oil (8007-20-3)	
Persistence and degradability	Rapidly degradable
COUMARIN (91-64-5)	
Persistence and degradability	Rapidly degradable
Dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Rapidly degradable
Toluene (108-88-3)	
Persistence and degradability	Rapidly degradable
Camphene (79-92-5)	
Persistence and degradability	Rapidly degradable
Citrus medica limonum (Lemon) peel oil (8008-56-8)	
Persistence and degradability	Rapidly degradable
Cinnamalva (1885-38-7)	
Persistence and degradability	Rapidly degradable
Allyl heptanoate (142-19-8)	
Persistence and degradability	Rapidly degradable
Linalool (78-70-6)	
Persistence and degradability	Rapidly degradable
Ethyl acetoacetate (141-97-9)	
Persistence and degradability	Rapidly degradable
12.3. Bioaccumulative potential	
FIREPLACE #EU34857F	
Bioaccumulative potential	Not established.
benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 25 °C)
Bioaccumulative potential	Not established.
Cedryl acetate (77-54-3)	
Partition coefficient n-octanol/water (Log Pow)	6 (at 25 °C)
1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone (54464-57-2)	
Partition coefficient n-octanol/water (Log Pow)	5.65 (at 30°C)
Sandal Mysore Core (28219-60-5)	
Partition coefficient n-octanol/water (Log Pow)	3.8

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Vanillin (121-33-5)	
Partition coefficient n-octanol/water (Log Pow)	1.23 (at 22 °C)
Bioaccumulative potential	Not established.
Vertofix (32388-55-9)	
BCF - Fish [1]	(3920 dimensionless (organ w.w.))
Partition coefficient n-octanol/water (Log Pow)	5.6 – 5.9
Eugenol (97-53-0)	
Partition coefficient n-octanol/water (Log Pow)	1.83 (at 30 °C (at pH 5.5))
Cinnamic aldehyde (104-55-2)	
Partition coefficient n-octanol/water (Log Pow)	2.1065 (at 25 °C)
COUMARIN (91-64-5)	
Partition coefficient n-octanol/water (Log Pow)	≥ 1.91 – ≤ 1.51 (at 25 °C (at pH 7))
Dipropylene glycol monomethyl ether (34590-94-8)	
Partition coefficient n-octanol/water (Log Pow)	0.35 (at 25 °C (at pH 7))
Toluene (108-88-3)	
Partition coefficient n-octanol/water (Log Pow)	2.73 (at 20 °C (at pH 7))
Camphene (79-92-5)	
Partition coefficient n-octanol/water (Log Pow)	4.22 (at 37 °C (at pH 7.2))
Cinnamalva (1885-38-7)	
Partition coefficient n-octanol/water (Log Pow)	1.96
Allyl heptanoate (142-19-8)	
Partition coefficient n-octanol/water (Log Pow)	3.97 (at 20 °C (at pH 5.3))
Linalool (78-70-6)	
Partition coefficient n-octanol/water (Log Pow)	2.9 (at 20 °C (at pH 7))
Ethyl acetoacetate (141-97-9)	
Partition coefficient n-octanol/water (Log Pow)	0.8 (at 20 °C)
12.4. Mobility in soil	
No additional information available	
12.5. Results of PBT and vPvB assessment	
No additional information available	
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
FIREPLACE #EU34857F	
Other information	Avoid release to the environment.

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

benzyl benzoate (120-51-4)	
Other information	Avoid release to the environment.

Vanillin (121-33-5)	
Other information	Avoid release to the environment.






SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container in accordance with local/national laws and regulations.
Ecological waste information	: Avoid release to the environment.
HP Code	: HP8 - "Corrosive:" waste which on application can cause skin corrosion. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
UN 1760	UN 1760	UN 1760	UN 1760	UN 1760
14.2. UN proper shipping name				
CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL)	CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL)	Corrosive liquid, n.o.s. (CUPRESSUS FUNEBRIS WOOD OIL)	CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL)	CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL)
Transport document description				
UN 1760 CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL), 8, I, (E), ENVIRONMENTALLY HAZARDOUS	UN 1760 CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL), 8, I, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS	UN 1760 Corrosive liquid, n.o.s. (CUPRESSUS FUNEBRIS WOOD OIL), 8, I, ENVIRONMENTALLY HAZARDOUS	UN 1760 CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL), 8, I, ENVIRONMENTALLY HAZARDOUS	UN 1760 CORROSIVE LIQUID, N.O.S. (CUPRESSUS FUNEBRIS WOOD OIL), 8, I, ENVIRONMENTALLY HAZARDOUS
14.3. Transport hazard class(es)				
8	8	8	8	8
				
14.4. Packing group				
I	I	I	I	I
14.5. Environmental hazards				
Dangerous for the environment: Yes	Dangerous for the environment: Yes Marine pollutant: Yes EmS-No. (Fire): F-A EmS-No. (Spillage): S-B	Dangerous for the environment: Yes	Dangerous for the environment: Yes	Dangerous for the environment: Yes
No supplementary information available				


FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: C9
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 0
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P001
Mixed packing provisions (ADR)	: MP8, MP17
Portable tank and bulk container instructions (ADR)	: T14
Portable tank and bulk container special provisions (ADR)	: TP2, TP27
Tank code (ADR)	: L10BH
Vehicle for tank carriage	: AT
Transport category (ADR)	: 1
Special provisions for carriage - Operation (ADR)	: S20
Hazard identification number (Kemler No.)	: 88
Orange plates	: 
Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 274
Limited quantities (IMDG)	: 0
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P001
Tank instructions (IMDG)	: T14
Tank special provisions (IMDG)	: TP2, TP27
Stowage category (IMDG)	: B
Stowage and handling (IMDG)	: SW2
Properties and observations (IMDG)	: Causes burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Forbidden
PCA limited quantity max net quantity (IATA)	: Forbidden
PCA packing instructions (IATA)	: 850
PCA max net quantity (IATA)	: 0.5L
CAO packing instructions (IATA)	: 854
CAO max net quantity (IATA)	: 2.5L
Special provisions (IATA)	: A3, A803
ERG code (IATA)	: 8L

Inland waterway transport

Classification code (ADN)	: C9
Special provisions (ADN)	: 274
Limited quantities (ADN)	: 0
Excepted quantities (ADN)	: E0
Carriage permitted (ADN)	: T
Equipment required (ADN)	: PP, EP
Number of blue cones/lights (ADN)	: 0

Rail transport

Classification code (RID)	: C9
Special provisions (RID)	: 274
Limited quantities (RID)	: 0
Excepted quantities (RID)	: E0
Packing instructions (RID)	: P001

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Mixed packing provisions (RID)	: MP8, MP17
Portable tank and bulk container instructions (RID)	: T14
Portable tank and bulk container special provisions (RID)	: TP2, TP27
Tank codes for RID tanks (RID)	: L10BH
Special provisions for RID tanks (RID)	: TU38, TE22
Transport category (RID)	: 1
Hazard identification number (RID)	: 88

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(a)	Cedar leaf oil ; Lemon oil	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F
3(b)	FIREPLACE #EU34857F ; Benzyl benzoate ; CUPRESSUS FUNEBRIS WOOD OIL ; Cedryl acetate ; Cedarwood oil, Virginia ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Sandal Mysore Core ; Vertofix ; Eugenol ; Cinnamic aldehyde ; Cedar leaf oil ; Lemon oil ; Cinnamalva ; Allyl heptanoate ; Linalool	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	FIREPLACE #EU34857F ; Benzyl benzoate ; CUPRESSUS FUNEBRIS WOOD OIL ; Cedryl acetate ; Cedarwood oil, Virginia ; 1-(1,2,3,4,5,6,7,8-Octahydro-2,3,8,8-tetramethyl-2-naphthalenyl)ethanone ; Sandal Mysore Core ; Vertofix ; Cinnamic aldehyde ; Cedar leaf oil ; Lemon oil ; Allyl heptanoate	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1
48.	Toluene	Toluene

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (2024/590)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 2024/590 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

VOC Directive (2004/42)

VOC content : 1.201574 % (calculated value)(CARB VOC) (%w/w)

Explosives Precursors Regulation (EU 2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (EC 273/2004)

Contains substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

Name	CN designation	CAS-No.	CN code	Category, Subcategory	Threshold	Annex
Toluene		108-88-3	2902 30 00	Category 3		Annex I

National regulations

France

Occupational diseases	
Code	Description
RG 4 BIS	Gastrointestinal disorders caused by benzene, toluene, xylenes and all products containing them
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

VOC ordinance (ChemVOCFarbV) : VOC content : 1.201574 % (calculated value)(CARB VOC) (%w/w)

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1).

List of sensitizing substances (TRGS 907) : Contains sensitizing substances according TRGS 907.

Major Accidents Ordinance (12. BImSchV) : Is not subject to the Major Accidents Ordinance (12. BImSchV)

Netherlands

ABM category : A(1) - highly toxic for aquatic organisms, may have longterm hazardous effects in aquatic environment

SZW-lijst van kankerverwekkende stoffen : CUPRESSUS FUNEBRIS WOOD OIL, Cedarwood oil, Virginia, Lemon oil are listed

SZW-lijst van mutagene stoffen : CUPRESSUS FUNEBRIS WOOD OIL, Cedarwood oil, Virginia, Lemon oil are listed

SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : Toluene is listed

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Denmark

Classification remarks

Danish National Regulations

- : Emergency management guidelines for the storage of flammable liquids must be followed
 - : Young people below the age of 18 years are not allowed to use the product
 - : Pregnant/breastfeeding women working with the product must not be in direct contact with it.
- If an employee is pregnant or breastfeeding and the person in question uses or is exposed to this product at work, the employer must always carry out a risk assessment of the work. The assessment must both deal with the dangerousness of the impact and its strength and duration. The employer's decision that a pregnant or lactating woman can perform a specific work task must therefore be made in the context of her specific working conditions. See also WEA-Guideline A.1.8-7 on the working environment of pregnant and breastfeeding workers.

Poland

Polish National Regulations

- : Act of 25 February 2011 on chemical substances and their mixtures (J. o L. No. 63, item 322 as amended; consolidated text J. o L. 2019, item 1225).
- : Act of 14 December 2012 on waste (J. o L. 2013, item 322 as amended; consolidated text J. o L. 2020, item 797).
- : The announcement of Marshal of the Sejm of the Republic of Poland dated 19 October 2016 concerning the consolidated text announcement of the decree on the management of packaging and packaging waste (J. o L. 2016, item 1863 as amended).
- : Decree of the Minister of Environment of 14 December 2014 on the catalogue of waste (J. o L. 2014, item 1923).
- : Act of 19 August 2011 on the Carriage of Dangerous Goods (J. o L. 2011 No. 227, item 1367 as amended; consolidated text J. o L. 2020, item 154).
- : Regulation of the Minister of Family, Labour and Social Policy of 12 June 2018 on the highest permissible concentration and intensity of noxious agents for health at work environment (J. o L. item 1286 as amended).
- : The announcement of Minister of Health dated 9 September 2016 concerning the consolidated text announcement of the decree of the Minister of Health of 30 December 2004 on health and safety at work related to exposure to chemical agents at work (J. o L. of 16 September 2016, item 1488)
- : Regulation of the Minister of Health of 2 February 2011 on tests and measurements of the noxious agents for health at work environment (J. o L. No. 33, item 166 as amended).
- : Regulation of the Minister of Environment of 9 December 2003 on particularly hazardous substances to the environment (J. o L. No. 217, item 2141).
- : ADR Agreement: Government Statement of 13 March 2023 on the entry into force of amendments to Annexes A and B to the Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), signed in Geneva on 30 September 1957 (J. o. L. 2023, item 891)
- : Regulation of the Minister of Health of 25 August 2015 on the method of marking places, pipelines, and containers and tanks used for storing or containing hazardous substances or hazardous mixtures (J.o.L. 2015, item 1368 as amended)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstracts Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disruptor

Other information : None.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1

FIREPLACE #EU34857F

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains {0 message≤name of sensitising substance> fieldvalue=_SENSITIZER_COMPONENTS}. May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Flam. Sol. 2	Flammable solids, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Corr. 1	Skin corrosion/irritation, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
Skin Sens. 1B	Skin sensitisation, category 1B
H226	Flammable liquid and vapour.
H228	Flammable solid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H361	Suspected of damaging fertility or the unborn child.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.